# Studying Curve Interpolator for CNC System

**Abbas M.Jabber Al-Fnzi*, Laith A.Mohammed***
**& Maan Aabid Tawfiq***

Received on :1/6/2008
Accepted on : 4/12/2008

**Abstract**

This thesis focuses on developing algorithm to calculate best length line segments in (u) and (w) directions. By of tool paths for free form surfaces based on the required accuracy of the manufactured part, which is represented by mathematical curves and surfaces. Bezier method was used to apply the proposed algorithms. The proposed algorithms consist of two parts; the first part is to calculate the better length line segment in (u) direction between cutter contact points (CC), the second part is to calculate the better line segment in (w) direction depending on the type of surface, cutter radius, tolerance and height scallop being given. The algorithms are applied in production field such as design of extrusion dies using three types of curve interpolation such as approximation cubic Bezier, interpolator Bezier and compound-CRHS profile die. In this paper, the manufactured parts are machined using a 3-axis CNC milling machine. The machining operations are simulated using SURFCAM software depending on the different interpolation techniques mentioned. An evaluation test is applied to the three interpolation methods based on Finite Element Method (FEM) using ANSYS 9.0 software to expect the strain and force required to extrude billet through the dies which are designed using the three mentioned interpolation methods. The G-code programs have been implemented on 5-axis CNC machine (Okuma VH-40-HS dynamic machine), the sample material is (cibatool) and the machining process is achieved without a lubricant at the Protoshop Oy in Helsinki/Finland.

**Keywords:** Curve Interpolator, CNC System, Bezier technique, CAD/CAM, G-code

## دراسة استكمال المنحني لنظام مكائن السيطرة الرقمية

**الخلاصة**

يركز هذا البحث على تطوير خوارزمية لحساب أفضل طول قطعة مستقيم في اتجاه (u) و (w). مسار العدة للسطح يعتمد على الدقة المطلوبة للجزاء المصنع, اي هو ممثل بواسطة الاقواس والسطوح الرياضية. طريقة بيزر هي الطريقة المستخدمة لتطبيق الخوارزمية عليها. الخوارزمية المقترحة تتكون من جزأين, الجزاء الاول هو حساب افضل طول قطعة مستقيم في اتجاه (u) بين نقاط تماس عدة القطع (cc), الجزاء الثاني حساب طول قطعة المستقيم الامثل في اتجاه (w) بالأعتماد على نوع السطح وكذلك على نصف قطر عدة القطع والتجاوز و(height scallop) المعطى. الخوارزمية المقترحة تم تطبيقها في مجال الأنتاج ( تصميم قوالب البثق) بواسطة استخدام ثلاثة انواع مختلفة من الأقواس المستكملة هي (cubic Bezier, interpolator Bezier and compound-CRHS extrusion profile die). في هذا البحث الاجزاء المصنع هي مشغلة بواسطة استخدام ماكنة تفريزCNC ذات ثلاثة محاور3-axis وذلك لغرض أستكمال الطرق وتحليلها ومقارنتها. حيث تم ايجاد طريقة تتجنب حدوث (gouging) خلال استخدام هذه الماكنة. تم

* Production and Metallurgy Department Engineering ,University of Technology/Baghdad



PDF created with pdfFactory Pro trial version www.pdffactory.com

محاكاة عمليات التشغيل باستخدام برنامج يدعى (SURFCAM) لمختلف الطرق المستكملة من اجل تقييم وتخمين السطوح قبل تشغيلها. تم أستخدام طريقة العناصر المحددة (FEA) للتقييم طرق الاستكمال الثلاثة من خلال استخدام برنامج ( ANASYS 9.0) من اجل التعرف على الانفعالات والقوى المطلوبة لبثق المعدن خلال القوالب المستكملة الثلاثة. ان برنامج (G-code) تم تطبيقه على ماكنة ذات خمس محاور(Okuma VH-40-HS dynamic machine) ,المادة التي تم تشغيلها هي (cibatool), وأن التشغيل تم بدون سائل تبريد في مصنع (Oy) في فنلندا(Helsinki/Finland).

## 1. Introduction:

The input to which system will be two (2D) or three dimension (3D) model. The model of the input contains not only dimensions of the shape but also the tolerance, height scallop, better length segment and special features. To facilitate a CAD, CAM system in the manufacturing process, we generate a NC program extrusion die design. The algorithm is applied to the extrusion die and the proposed algorithms (interpolator Bezier profile die) will be compared with cubic Bezier and component (CRHS) profile die. A real part is machined using SURFCAM software to simulate the part machining before machining on the CNC machine. We refer to G-codes as the machine language output from SURFCAM software in this research. After determining the length line segment and comparing between cubic Bezier, interpolator cubic Bezier and component (CRHS) profile die, we calculate the homogenous strain and force required for extrusion die utilizing the ANASYS 9.0 software.

Theories and algorithms which relate shapes and geometries of CAD models to the path and motion controls of CNC machine tools constitute a subject area called motion intelligence. This area of concern consists mainly of three categories [1]: Curve and surface containing the all features being mentioned.In this work (DXF-file) shall be converted from MATLAB to SURFCAM software to visualize the product before machining. In this work, we propose a modified methodology will be proposed to calculate segments of appropriate length in (u,w) directions that are within the tolerance, height scallop and ultimately generate the tool path for presentation, tool path generation approaches and surface machining approaches. Many researches have been done for represent curve and surface. **Thilo Kielmann (2007)** [2] investigated computer graphics curves and surfaces**.** In this research, he studied mathematical representation of curves (explicit, implicit, and parametric), the representation of parametric surfaces for quadratic and cubic polynomial. He studied cubic interpolation and joining interpolating segments. The study is applied to Hermit, Bezier and B-Spline curves and surfaces. **Akeel S. Bedan (2006)** [3] investigated automation surface generation from wireframe data in CAD application. He created an efficient and accurate 3D surface interior data depending on primary initial data based on approximation and interpolation techniques. The research presented a mathematical algorithm to generate 3D surface design using three different



PDF created with pdfFactory Pro trial version www.pdffactory.com

approximation methods (Hermit, Bezier and B-Spline technique). A comparison has been made between the two adopted techniques of surface generation (approximation and interpolation) depending on several standard functions (sine-cosine functions, exponential functions, parabola functions, fractional functions and polygons). Many researches have been done for represent tool path generation approaches. **Young-Keun Ehoi et al (2007**) [4] investigated tool path generation and tolerance analysis for free-form surfaces**.** They focused on developing algorithms that generate tool paths for free-form surfaces based on the accuracy of a desired manufactured part. A manufacturing part is represented by mathematical curves and surfaces. This algorithm reduces manufacturing and computing time as well as the (CC) points while keeping the given tolerance and scallop height in the tool paths. **His-Yung Feng et al (2002)** [5] studied constant scallop-height tool path generation for three-axis sculptured surface machining**.** They present a new approach for the determination of efficient tool paths in the machining of sculptured surface using 3-axis ball end milling. The objective was to keep the scallop height constant across the machined surface such that redundant tool paths are minimized. Their work determines the tool paths without resorting to the approximated 2D representation of the 3D cutting geometry. Two offset surfaces are employed to successively establish scallop curves on the scallop surface and cutter location tool paths for the design surface. The results indicate the constant scallop-height machining achieves the specified machining accuracy with fewer and shorter tool paths than previous path generation approaches. ). **D.K. Pratihar et al (2005)** [6] studied optimization of CNC isoscallop free form surface machining using a generate algorithm. They presents isoscallop machining with edge-based master cutter path (MCP), which essentially ensures uniformity of surface, roughness over entire surface of part but may not necessarily ensure minimization of machining time. In their work it has been shown that there is a provision for minimizing machining time while implementing isoscallop machining by optimizing the orientation of the primary or master (MCP) through application. The results indicate substantial reduction in total machining time for the proposed approach compared to those obtained through previously reported cutter path generation strategies. **Jianguo Wang (2005)** [7] investigated global finish curvature matched machining. The thesis focuses on how to determine the uncut or rework areas of the previous CM2 (curvature matching machining) and how to define the boundary of these regions. Strategies for generating more efficiency CM2 tool paths are also discussed. The goal was to improve surface finish and achieve design surface dimensions more accurately.

**2. Bezier Representation:** P. Bezier of the French automobile company of Renault first introduced the Bezier curve**.** A system for designing sculptured surfaces of automobile bodies (based on the Bezier curve) was introduced in (1962) [8]. Bezier has chosen a family of functions called 'Bernstein polynomials' to



PDF created with pdfFactory Pro trial version www.pdffactory.com

satisfy these properties. Bezier started with the principle that any point on a curve segment must be given by parametric function of the following form where (u and w) are surface parameters, Bi,n is Bezier coefficient [9]:

$$P(u) = \sum_{i=0}^{n} P_i B_{i,n}(u)$$

$u \in [0,1]$..... .....( 1)

where the basic functions are:

$$B_{i,n}(u) = \binom{n}{i} u^i (1-u)^{n-i}$$

$$B_{i,n}(u) = \frac{n!}{i!(n-i)!} u^i (1-u)^{n-} \quad \text{. . (2)}$$

**3. Algorithms Proposed For Representing Interpolator Curve for CNC System Approach:-**

In this section, we will summarize algorithms proposed that can be used to calculate optimum length of line segment with tolerance given and calculating better side step with given height scallop.

*** Defining the Designed Surface in the (u,w) Direction:**

The designed part is represented by Cubic Bezier surface. The surface is represented by parameterized over a domain (u,w) and defined by parallel curves called isoparametric curves. Boundary of curves must be equal to the boundaries of the surface.

*** Calculating the Radius of Curvature:**

On the designed part, we calculate the radius of curvature at each point on the surface to obtain the minimum radius of curvature. Calculating the radius of curvature very important because it is used to determine the length of line segment and determining better cutter radius must be equal to or smallest than the minimum radius of curvature to avoid gaouging and interferance for the parametric surface.

*** Calculating The Optimum Line Segment in (u,w) Direction With Scallop Height and Tolerance Given:**

During surface machining, the surface part is approximated by series of line segments. Therefore in this thesis, we calculate the length of line segment in (u) and (w) direction. We approximate the tool path by better length segment (linear interpolation). The better length segment is the distance between (CC) points during current tool path with in the limited given tolerance. This work will determine the length line segments for forward step (L). After calculating length line segment in (u) direction, we calculate the better length segment in (w). Length line segment in (w) direction is the better distance between two adjacent tool paths which can keep the height scallop (h) given. Hence the radius of tool must be less than or equal to the minimum radius of curvature. The side step (g) is a function of the scallop height (h), tool radius and the local radius of the curvature (ρ); therefore three different cases are considered to calculate side-step size (g) [11]:



PDF created with pdfFactory Pro trial version www.pdffactory.com

1- A flat surface as shown in figure (3A):

$$h = r - \sqrt{r^2 - (\frac{g}{2})^2}$$

$$g^2 = 4r^2 - 4(r-h)^2$$

$$g = 2\sqrt{r^2 - (r-h)^2} \quad .....(3)$$

2- A convex curvature is shown in figure (3B).

$$d = OB - OA$$

$$OA = \sqrt{r^2 - p^2}$$

$$OB = r$$

$$h = r - \sqrt{r^2 - p^2 + d}$$

$$g = 2 - \sqrt{r^2 - (r + d - h)^2} \quad .....(4)$$

3- For a concave curvature as shown in figure (3C) we calculate the step size for concave surface:

$$d = OB - OA$$

$$OA = \sqrt{r^2 - p^2}$$

$$OB = r$$

$$h = r - \sqrt{r^2 - p^2 - d}$$

$$g = 2 - \sqrt{r^2 - (r - d - h)^2} \quad ...(5)$$

Where (ρ) is the local radius of the curvature surface .Using the above equations, (g) is calculated at each point on the current curve [11].

*** Converting the Length Line Segment in (u,w) Direction into Parametric Domain:**

The length line segment in (u,w) direction is determined by a physical unit, therefore it must be converted into the parametric system (u,w) to represent different surface in the machining.

*** Converting (CC) Point to (CL) Points:**

The (CC) points must be converted to the (CL) points to generate tool path and manufacture part. (CL) are stored as a (CL) data file. After these steps we calculate strains and forces for interpolator Bezier profile die then compare the results with cubic Bezier and compound-CRHS profile die.

**4. (CRHS) Dies:-**

The principles and techniques used in the design of tools according to the CRHS concept are discussed below. Four basic rates of deformation (S) for CRHS profile dies are adopted in this investigation [13]:

- S= 0.8 for decelerated rate of deformation.
- S = 1 for uniform rate of deformation.
- S = 1.2 for accelerated rate of deformation.
- S= (0.8 + 1 + 1.2) compound rate of deformation.

The concept of the (CRHS) depends on homogenous strain and neglected elastic strain because elastic strain is little mounted

$$z_1 = (\frac{R0}{Rn})^2 .....(6)$$

$$z_n = (z_1)^{s^{(n-1)}} * (z_{n-1})$$

$$z_n = (z_1)^{s^1} * z_1$$

$$z_3 = (z_1)^{s^2} * z_2 = (z_1)^{s^2} * (z_1)^{s^1} * z_1 = z_1^{s^2+s+1} ..(19)$$

**5. Example of Proposed Algorithm:-**

The proposed algorithm must be implemented and tested with another case study (cubic Bezier, interpolate Bezier with component-CRHS profile die) and we calculate



PDF created with pdfFactory Pro trial version www.pdffactory.com

the appropriate (CC) points by using proposed algorithm. The software used in this proposed algorithm is:
* MATLAB 7.4.
* SURFCAM.
*ANSYS 9.0.
The proposed algorithms are performed on a personal computer (Core, 1.663 2CPU, 512 Mb of Physical Memory) with Microsoft XP professional. The desired surface was generated by MATLAB (7.4) software.

**A. Case Study (Cubic Bezier Profile Die):**

Tool path resolution (length line segment) is related to machining tolerance. The machining efficiency of tool paths is directly related to the machining time. Machining time is typically proportional to manufacturing costs. Figure (6) shows control polygon, cubic Bezier profile die, and represents zig-zag tool path. After we explain and visualize of cubic Bezier profile die SURFCAM software will be used to simulate machining of Bezier profile die and tool path achieved by MATLAB (7.4) software. DXF-file is used to convert profile die and tool path from MATLAB (7.4) to SURFCAM. Two milling cutters are used in roughing process; the cutter diameter is (16 mm) to reduce machining time. After this process better cutter radius (cutter radius doesn't exceed the minimum radius of curvature) is used to apply finishing process by using (5mm) cutter diameter. Cibatool is the material selected in this recearch. Figure (7) shows machining extrusion die (Cubic Bezier profile die) by using SURFCAM software.

**B. Case Study (Interpolator Cubic Bezier Profile Die):**

Figure (8) represents interpolator Bezier (representing extrusion profile die), and represents the tool paths for interpolator Bezier surface with allowed tolerance, height scallop and length line segment. After determining length line segment for interpolator Bezier profile SURFCAM will be used to simulate machining for proposed algorithms. Figure (9) shows machining extrusion die (interpolator Bezier surface) by using SURFCAM. Figure (9A) shows the workpiece (cibatool) before maching (block), Figure (9B) shows the roughing operation for model (using 16mm cutter diameter) and Figure (9C) shows the finishing operation for the designed model (using 5mm cutter diameter).

**C. Case Study (Compound-CRHS Profile Die):**

After the use of a cubic Bezier surface and Interpolator Bezier surface for extrusion die design, we will now focus on compound (CRHS) dies design. Compound (CRHS) consists of three sections, of which the first section is designed according to the (ACRHS) concept, while the mid of the die is designed according to the (UCRHS) concept. And the end section is designed according to the (DCRHS) concept as shown below such as shown in the figure (10).

**6. Extrusion Force:**

Strain and force required in each extrusion die will be calculated to determine better extrusion die



PDF created with pdfFactory Pro trial version www.pdffactory.com

(strain and force needed to extrude billet). For simulation of the extrusion dies process by using commercial ANASYS 9.0 software we used element SOLID 45, aluminum material properties, model generation within ANASYS (direct generation used in this research), meshing model (mapped), contact surface (target surface TARGE 170 and contact surface CONTA 174 used in this research), pilot point to control the boundary conditions and motion of the entire target surface. Extrusion die processes consist of four parts they are Rim, billet, container and die.

The force required for extrusion depends on the flow stress of the billet container interface, the friction condition at the die material interface, and the other process variables, such as initial billet temperature and speed extrusion. The required extrusion force (F) is given by:

$$F=P*A \qquad \text{..... (7)}$$

where:

- **P=** extrusion pressure.
- **A=** area of the container bore.

Figure (12) show the force (N) with displacement (mm) for proposed algorithm compared with cubic Bezier and compound-CRHS profile die.

## 7. Cutting Conditions for Interpolator Extrusion Die:

Our fabricating work is of experimental nature. The material that was used is (cibatool) .The tool used in this work is tip ball mill cutter, tool material is (HSS) with Ø16mm roughing process and Ø5mm to finishing process applied to interpolator Bezier profile die, the machining was achieved on CNC machine (Okuma VH-40-HS dynamic 5-axis CNC machine, with specification of linear motor drives (10.000 m/min), motor spindle 7.5KW 8000 rpm), machine control OSP 7000 M. The machining process is achieved at the Protoshop Oy in Helsinki/Finland as shown in figure (13), and the G-codes applied to the CNC machine were achieved by using SURFCAM. The G-code was designed by 3-axis FANUC 15 MB system, and the machining process was done without a lubricant.

## 8. Conclusions:

The proposed algorithm for interpolator cubic Bezier surface developed and implemented successfully through the integration of mathematical modeling used for calculations near optimum length line segment for free form surface with given tolerance and height scallop.

The advantages of the proposed system are summarized as follows:

1- The Bezier technique is regular, easy to derive and by changing control points to represent different types of extrusion dies comparable to CRHS profile dies.

2- Interpolator Bezier profile die has a tolerance (0.01mm) in (u) direction, which is less than for the cubic Bezier profile die within (%84.375)



PDF created with pdfFactory Pro trial version www.pdffactory.com

and within (87.99) for the compound-CRHS profile die.

3- Interpolator Bezier profile die has a tolerance (0.01mm) in (w) direction, it has a tolerance less than cubic Bezier and compound-CRHS profile die within (%95).

4- Interpolator Bezier profile die has height scallop (0.04mm), it has less height scallop than cubic Bezier and compound-CRHS profile die within (%33).

5- The selection of better cutter radius depends on the minimum radius of curvature (not to exceed the minimum radius of curvature).

6- Zig-zag tool path generation is the better tool path compared to isoparametric and isoscallop tool paths.

7- We employ DXF-files to convert cubic Bezier, interpolator Bezier and compound-CRHS profile die from MATLAB (as CAD tool) to SYRFCAM (as CAM tool) and to obtain the G-code functions and simulate the machining process. The algorithms proposed generate (6569) blocks of G-code, which is has more than for cubic Bezier profile die within (%16) and within (%32.37) for compound-CRHS profile die.

8- A ball end-mill is a better tool in machining profile die compared to a flat and a bullnose end-mill.

9- Time secondary operations (grinding and polishing) are reduced through determining the appropriate line segment.

10- We can reduce the error during machining by using a 5-axis machine.

11- Interpolator Bezier profile die gives better surface quality because it is better than cubic Bezier profile die within (%74) and than compound-CRHS within (%66).

12- Force required to extrude the metal (aluminum) during interpolator Bezier profile die is equal to (100786 N), it has more than cubic Bezier profile die within (%8.5) and less than compound-CRHS within (%3.8).

**References:**

[1]-Hong Liang , "Minimum error tool path generation method and interpolator Design technique", Ph.D, thesis Department of Mechanical Engineering, Concordia University, Canada,1999.

[2]-Thilo Kielmann ,"Computer graphics curves and surfaces ", University of Pennsylvania, 2007.

[3]- Akeel S. Bedan , "Automatic Surface generation from wire frame Data in CAD Applications", M.Sc thesis, Department Of Production Engineering and Metallurgy,University Of Technology, 2006.

[4]-Young – Kenn choi & A. Banerjee, "Tool Path generation and tolerance analysis for free form surfaces", International Journal of Machine Tools & Manufacture, 2007.

[5]-Hsi-Yung Feng & Huiwen Li, "Constant scallop height tool path generation for three–axis sculptured surface machining" , Computer–



PDF created with pdfFactory Pro trial version www.pdffactory.com

Aided Design, vol.34, pp.647 – 654. 2002.
[6]-D.K.Pratihar et al, "Optimization of CNC iso-scallop free form surface machining using a genetic algorithm", International Journal of Machine Tools & Manufacture, vol.46. pp.811 – 819.2006.
[7]- Jianguo Wang," Global finish curvature matched", M.Sc. thesis Department of Mechanical Engineering, Brigham Young university, , 2005.
[8]-Gray Wang, "025.353 Computer Aided Design and Analysis Course Notes", Dept. of Mechanical and Industrial Engineering the University of Manitoba, Cancopy, 2000. http://www.umanitoba.ca/faculties/engineering/mech_and_ind/prof/wang/index_files/25.353/index.html
[9]-Michael E. Mortenson, "Geometric Modeling", John Wiley and Sons, Inc. 1997.
[10]-Yan-Shine Lee, et al, "Rolling-Ball Method and Contour Marching Approach To Identifying Critical Regions For complex Surface machining ", computer in industry, vol, 41. pp.163-180. 2000.
[11]-Young Keun Chio, "Tool path Generation and 3D Tolerance Analysis for Free Form Surface", Ph.D, thesis Department of Mechanical Engineering, Texas A&M University.2004.
[12]-Debananda Misra et al, "Zig-zag Tool path Generation For Sculptured Surface Finishing ", Department of Mechanical Engineering, University of California, Berkeley, CA, USA, 2004.
[13]- Abdul Kareem Jalleel Kadhim, "Assessment of die design and manufacturing preparation for the extrusion of elliptical sections from round billets", Ph.D, thesis submitted to Department of Production Engineering and Metallurgy, University of Technology, 2004.
[14]-Wissam Kadhim Hamdan, "Three Axis Interpolation and Emulation for Computerized Numerically Controlled Milling Machines", M.Sc, thesis Department of Production Engineering and Metallurgy, University of Technology, 2001.
[15]-Young Kenn choi et al, "Tool Path generation and tolerance analysis for free form surfaces", International Journal of Machine Tools & Manufacture, vol. 47. pp.689-696. 2007.
[16]-Gyula Hermanu, "Real-Time 3D tool path generation for numerical control ", johnvon nenmann faculty of information technology, 2000. http://www.bmf.hu/conferences/SAMI2004/Hermann.pdf
[17]-Sotiris L. omirou et al,"Integrate of new programming capabilities into a CNC milling system", Robotics and Computer-integrated Manufacturing, vol. 21. pp. 518-527. 2005.
[18]-Erik Oberg et al," 26th Edition Machinery's Handbook", Industrial Press Inc.2000.
[19]-Steve Krar & Arthur Gill, "Computer Numerical Control Programming Basics",Industrial Press, Inc.1999. http://www.industrialpress.com/en/portals/0/Books/31314/31314.pdf
[20]- Hayder K. Al-Abedi," Development of the free form surface construction approach by using computer", MS.c, University Of Technology, Department Of Production Engineering and Metallurgy, 2002.
[21]- Kaspar Fischer," Piecewise Linear Approximation of Bezier Curves", Computer-Aided Design, 2001.



PDF created with pdfFactory Pro trial version www.pdffactory.com

[22]-Anders Iglesias, "Bezier curve and surfaces", University of Contabria, Department of Applied Mathematics and Computational Sciences, 2001.
[23]-Anders Iglesias, "High level computation programs mathematical and MATLAB in CAGD and computer graghics ", Department of Applied Mathematics and Computational Sciences, University of Contabria, 2001.
[24]-Kenth I. Joy, " Quadratic Bezier curves", Department of Computer Science,University of California, , Davis, 2000
[25]- Sung-Gun Lee et al, "Mesh-based tool path generation for constant scallop-height machining", Springer-Verlag, DOI 10.1007/s00170-007-0943-x. 2007.
[26]-L.P. Zhang, et al, "Tool path regeneration for mold design modification ", computer – Aided Design, vol.35. pp. 813-823. 2003.
[27]-Sang C. Park "Tool-path generation for Z-constant contour machining" computer Aided Design, vol.35. pp. 26-36.2003.
[28]-Eungki Lee, "Contour offset approach to spiral tool path generation with constant scallop height", Computer – Aided Design, vol.35. pp.511-518. 2003.
[29]- C. Lartigue et al, "CNC tool path in terms of B–spline curves", Computer–Aided Design, vol.33, pp.307 – 319. 2001.
[30]- G. kiswanto et al," Gouging elimination through tool lifting in tool path generation for five-axis milling based on faceted models", Springer-Verlag, vol. 32. pp.293-309.2007.
[31]- Jenq–Shyong Chen et al, "A study of the surface scallop generating mechanism in the ball–end milling Process", International Journal of Machine tools & Manufacture, vol.45. pp.1077 – 1084.2005.
[32]- Eing – Jer Wei et al, "Study on general analytical method for CNC machining the Free – from surfaces", Journal of Materials processing technology, vol. 168.pp. 408 – 413.2005.
[33]-Diaa F. Elkott et al," Isoparamtric line sampling for inspection planning of sculpture surfaces", Computer-Aided Design, vol.37. pp.189-200. 2005.
[34]- Marchenko Tikhon et al, "NURBS interpolator for constant materials rate in open NC machine tools", Intentional Journals of Machine Tools Manufacture, vol.44. pp. 237-245. 2004.
[35]-Zezhong C. Chen et al, " Automated surface subdivision and tool path generation for 31/21/2 axis CNC machining of sculptured pants ", Computer in Industry, vol. 50.pp.319-331. 2003.
[36]-Tao Chen & Piecing Ye "A tool path generation strategy for sculptured surfaces machining", Journal of Maternal Processing Technology, vol. 127. pp. 369-363. 2002.
[37]-S. Mansour, "Automatic generation of part programs for milling sculptured surfaces", Journal of Materials Processing Technology, vol. 127. pp. 31-39. 2002.
[38]-Cha – Soo Jun el at, "Anew curve based approach to polyhedral machining", Computer Aided Design, vol. 34. pp. 379-389. 2002.
[39]- Seok – Hyung Bae et al, "Automatic feedrate adjustment for pocket machining ", Computer – Aided Design, vol.35. pp.495– 500. 2003.
[40]- B O H. Kim & Byoung K. choi, "Machining efficiency comparison



PDF created with pdfFactory Pro trial version www.pdffactory.com

direction – Parallel tool path with contour – Parallel tool path", Computer – Aided Design, vol.34. pp. 89 – 95. 2002.
[41]-Yuan – Shin Lee et al," Rolling – ball method and contour marching approach to identifying critical regions for complex surface machining", computer industry, vol.41. pp. 163-180. 2000.
[42]-Chih – ching Lo, "CNC machine tool surface interpolator for ball – end milling of free form surfaces", International Journal of machine Tools and manufacture, vol.40. pp. 307 – 326. 2000.
[43]-Vera B.Anand, "Computer Graphics and Geometric Modeling for Engineering", Jon Wiley and Sons, Inc.1993 .
[44]-The numerical methods, Inc. "Interpolation", http://www.numerical methods. eng. Usf. edu.
[45]-The Mathworkes Inc., "Interpolation", http://www.mathworks.com/moder/interp.pdf.
[46]-M.Alberti et al, "Experimental analysis of dimensional error vs cycle time in high speed milling of aluminum alloy", Internationals Journal of machine tools & manufacture, vol. 47, pp.236-246. 2007.
[47]-Erik L.J Bohez & Ms. Busaba Limsombutanan, "Curvature Analysis Based Hole on for 5-axis Milling Cutter Selection and Tool path Planning ", Asian Institute of Technology .1998.
[48]-Richard H. Bartels et al, "An introduction to splines for use in computer graphics and geometric modeling",Morgan Kaufmaun Publishers, Inc. 1987.
[49]-Daoyuan Yu et al, "Flat End Cutter Path Generation For A sculptured Surface For 3-axis NC Machining", Journal of Materials processing technology, vol.57. pp. 65-69. 1996.
[50]-Z. Y. Zhoo et al, "Pocketing tool path optimization for sharp corners", Journal of Materials Processing Technology, vol.192-193. pp. 175-180. 2007.
[51]-Mahadevan Balasubramaniam, "Tool selection And Path Planning for 3-axis Rough Machining ", M.Sc, thesis Indian Insitute of Technology, Madras, 1999.
[52]-Rong-Shine Lin, "Real-Time Surface Interpolator for 3-D Parametric Surface Machining On 3-axis Machine Tools " , International Journal of Machine tools & Manufacture, 2000.
[53]-Shakir Madlwm Katee, "Studying the effect of normal anisotropy on deep drawing operation using finite element method", M.Sc. Thesis submitted to Department of Production Engineering and Metallurgy ,University of Technology, 2007.
[54]- A. F. Shahab, "Investigation of the pass Geometry in compound backward– Forward Extrusion Process", Ph.D, thesis Department of Production Engineering and Metallurgy, University of Technology, (2005).
[55]-Jain Sanjay Jain, "Principles of automation and advanced manufacturing systems", Chandni Mahal, Delhi, 2004.
[56]- Mukdam Habib S. kena, "Analysis and Application of SubdivisionSurfaces", M.Sc, thesis Department of Production Engineering and Metallurgy, University of Technology, 2007.



PDF created with pdfFactory Pro trial version www.pdffactory.com

- **Table below shows summary of machining parameters for cubic Bezier, interpolator Bezier and compound-CRHS profile dies.**

| No. | Profile Die | | | |
|---|---|---|---|---|
| | Properties | Bezier Profile Die | Interpolator Bezier Profile Die | Compound-CRHS Profile Die |
| 1 | Tolerance in (u)and(w) direction | 0.064 & 0.2 mm | 0.01 & 0.01 mm | 0.0833 & 0.2 mm |
| 2 | Height Scallop | 0.06 mm | 0.04 mm | 0.06 mm |
| 3 | Minimum Radius of Curvature | 1.948 mm | 1.948 mm | 1.949 mm |
| 4 | Radius of Cutter (Roughing) | 8 mm | 8 mm | 8 mm |
| 5 | Radius of Cutter (Finishing) | 2.5 mm | 2.5 mm | 2.5 mm |
| 6 | Length Line Segment in (w) Dir. | 0.8 mm | 0.7 mm | 0.8 mm |
| 7 | Length Line Segment in (u) Dir. | variable | 0.3 mm | 1 mm |
| 8 | (CC) Points | 1080 | 4216 | 1404 |
| 9 | Number of Segment For Tool Path | 1295 | 3843 | 1619 |
| 10 | Number of Tool Path | 108 | 124 | 108 |
| 11 | Length of Tool Path | 330 m | 377.8 m | 333.8 m |
| 12 | Size Store in Memory in (Bytes) | 1229914 Bytes | 148738 Bytes | 131406 Bytes |
| 13 | Number of G-code | 5515 Blocks | 6569 Blocks | 4442 Blocks |
| 14 | Numbers of Cutter Flutes | 4 | 4 | 4 |



PDF created with pdfFactory Pro trial version www.pdffactory.com

| | | | | |
|---|---|---|---|---|
| 15 | Total Time of Machining (min.) | 197.471 | 226.074 | 199.745 |
| 16 | Time 0f finishing machining (min.) | 59.301 | 74.440 | 65.8836 |
| 17 | Max. Strain | 0.636 | 0.636 | 0.636 |
| 18 | Max. Force to Extrude Billet (N) | 92191 | 100786 | 104617 |




**Figure (1) Represents surface cubic Bezier extrusion profile die.**






**Figure (2) Local gouging on concave region [10].**



PDF created with pdfFactory Pro trial version www.pdffactory.com




**(A)** **(B)**

**(C)**

**Figure (3) Represent tool position on the: (A) Flat surface. (B) Convex surface. (C) Concave surface [11].**





**Figure (4) Inverse tool offset algorithm [12].**





**Figure (5) The geometric shape (for the Forward Extrusion) dies profile designed by CRHS.**



PDF created with pdfFactory Pro trial version www.pdffactory.com





**Figure (6) Representation of profile dies by using cubic Bezier surface (By using approximation length segment): (A) Control polygon. (B) Bezier profile dies. (C) Tool path for Bezier profile die.**







**Figure (7): Using SURFCAM software to simulate the machining of cubic Bezier profile dies. (A) Workpiece (cibatool).(B) Roughing process. (C) Finishing process.**



PDF created with pdfFactory Pro trial version www.pdffactory.com




(A) (B)




(C)

**Figure (8): Represents profile die by using interpolator Bezier surface (By using better length segment). (A)Control polygon. (B) Bezier profile dies. (C) Tool path for Bezier profile die.**



(A) (B)



(C)

**Figure (9): Using SURFCAM software to simulate the machining of interpolator Bezier surface (A) Workpiece (cibatool). (B) Roughing process. (C) Finishing process.**



PDF created with pdfFactory Pro trial version www.pdffactory.com








**Figure (10): Profile die by using compound-CRHS.**





**(A)**



**(B)**

**(C)**

**Figure (11): Using SURFCAM program to simulate the machining of compound-CRHS profile die. (A) Workpiece (cibatool). (B) Roughing process. (C) Finishing process.**



PDF created with pdfFactory Pro trial version www.pdffactory.com





**Figure (12): Represents force (N) with displacement (mm) for Cubic Bezier profile die, Interpolator Bezier profile die, Compound-CRHS profile die.**




**Figure (13): The machined models produced by CNC milling machine (3-axis). Sample designed by interpolator Bezier profile and machined with cutter diameter equal (roughing=16mm and finishing=5mm).**



PDF created with pdfFactory Pro trial version www.pdffactory.com